	à		
CERTIFICATE OF MAILING BY FIRST CLASS MAIL (37 CFR 1.8) Applicant(s): Yasushi AKIYAMA et al.			Docket No.
			2002ЈР311
Serial No.	Filing Date	Examiner	Group Art Unit
10/519,242	December 22, 2004	WU, Ives J.	1713
Dention: COMPOSIT	ION FOR ANTIREFLECTIVE CO	DATING AND METHOD FOI	R FORMING SAME
SEP 1 6 2005)			
হু			
& TRADBUARNO			
		ID (2.0(2520 - 2.D.))	
I hereby certify that this	s English Language abstract of	JP 62-062520 - 2 Pages (Identify type of correspondence)	
is being deposited wit	h the United States Postal Servi	ce as first class mail in an e	nvelope addressed to: The
Commissioner of Pate	nts and Trademarks, Washington	. D.C. 20231-0001 on	September 14, 2005
	The and Trademane, Traemington		(Date)
		MARIA T. SAI	NCUF7
		(Typed or Printed Name of Person N	
		11/2	26
		(Signature of Person Mailing	Correspondence S
	Note: Each paper must have	e its own certificate of mailing.	

PATENT ABSTRACTS OF JAPAN

(11) Publication number: 62-062520

(43) Date of publication of application: 19.03.1987

(51)Int.CI. H01L 21/30

G03F 7/20

G03F 9/00

H01L 21/302

H01L 21/68

TITTLE CITY OF

(21)Application number: 60-201524 (71)Applicant: HITACHI LTD

(22)Date of filing: 13.09.1985 (72)Inventor: TANAKA TOSHIHIKO

SHIRAISHI HIROSHI

HASEGAWA NOBUO

HAYASHIDA TETSUYA

(54) PATTERN FORMING METHOD

(57)Abstract:

PURPOSE: To form an ultrafine and accurate pattern and a pattern having high alignment accuracy by forming a perfluoroalkyl polyester film or perfluoroalkylamine film or their mixture film on a resist.

CONSTITUTION: A perfluoroalkyl polyether film, a perfluoroalkylamine film or their mixture film (perfluoroalkyl compound) is formed on a resist before exposing, and the perfluoroalkyl compound film is removed after exposing. The perfluoroalkyl compound film is transparent and its refractive index is approx. 1.3. Therefore, it serves as a resist reflection preventive film. Reflected light on the resist surface is reduced without loss of the incident light amount by the transparent reflection preventive film to prevent the pattern dimension accuracy from decreasing owing to the multiple interference of light in the resist film. It also reduces the deterioration of a pattern detection signal.

LEGAL STATUS [Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office